Circulating fluid temperature controller

THERMOCHILLER



5°C – 40°C
Adjustable temperature range

5l Storing Capacity

Silent (60db)

GIBERTINI

Via Bellini, 37
20026 Novate Milanese
(Milano) - italy

Tel. (+39) 023541434
info@gibertini.com
sales@gibertini.com

Characteristics

Space saving thanks to compact dimension and quiet operation(60 dB)
Low tank level detection function
Power failure auto-restart function
Anti-freezing operation function
Self-diagnosis function and check display
Easy and tool-less filter maintenance
Special executions available on request
Electronic temperature control and temperature reading on digital display
Integrated pump for recirculating of the cooled liquid
Mounted on pivoting wheels for easy movement

Operating Conditions

Ambient Temperature	5°C ÷ 40°C
Humidity	**30 ÷ 70 %**

Technical Specifications

Temperature range from	5°C ÷ 40 °C
Temperature stability	± 0,1°C
Tank capacity	5 litri
Power Supply	230V-1800 W – 50/60 Hz, other voltages on request
Dimensions (L x D x W)	38 x 50 x 62 cm
Net Weight	43 kg

Subject to technical changes without notice.
All our instruments are to be used exclusively for scientific purpose and/or for internal control only. They must not be used in environments with danger of explosions.
The use of our balances is forbidden in the cases provided by art. 1, point 2, letter a) of directive 2014/31/UE except for those models approved with CE mark (legal metrology).
Electronic balances are sensible to the variation of the acceleration of gravity. They must be calibrated on the working site (2014/31/UE).
All our instruments comply with directive 2014/30 UE (electromagnetic compatibility)

For further information, visit **www.gibertini.com**